


Zehnder ComfoWell 520



Comfowell 520

The Zehnder ComfoWell 520 is a modular system consisting of attenuators, fine grade filters and active carbon filters all integrated for use with a rigid or semi-rigid ductwork approach. With a width of 520mm it can be used for connecting up to 10 ComfoTube connections. The systems compact dimensions ensure good sound absorption and also make it easy to clean. Rigid pipe can be connected to the end plate securely by utilising the gasket seal connection. All other components are fitted using the locking slide connections to form an airtight and robust seal.

Noise reduction can be improved by combining two attenuators together. Filters are available in ISO ePM1 >80% (F7) or ISO ePM1 >90% (F9) grade in addition to an odour neutralising active carbon filter.





Key Features

- Attenuator, fine grade filter, active carbon filter and manifold all combined into one space saving combination with the option to bespoke build exactly what is required.
- Easy to assemble thanks to its modular and compact design.

Article Numbers	
Description	Product Code
Attenuator	
Zehnder ComfoWell attenuator, CW-S 520	990 323 502
Manifold	
Zehnder ComfoWell manifold box CW-D 520	990 323 532
Filter Housing	
Zehnder ComfoWell filter housing CW-F 520	990 323 552
Mounting Plates	
Zehnder ComfoWell mounting plate, CW-M 520, 10 x 75mm connections	990 323 614
Zehnder ComfoWell mounting plate, CW-M 520, 10 x 90mm connections	990 323 615
Zehnder ComfoWell mounting plate, CW-M 520, 4 x 90mm + 6 x 75mm connections	990 323 617
End Plates	
Zehnder ComfoWell end plate, CW-P 520, ø 150mm	990 323 568
Zehnder ComfoWell end plate, CW-P 520, ø 160mm	990 323 564
Zehnder ComfoWell end plate, CW-P 520, ø 180mm	990 312 513
Zehnder ComfoWell end plate, CW-P 520, ø 200mm	990 312 514

Article Numbers

Spacer Frame	
Zehnder ComfoWell spacer frame, CW-DF 520	990 323 539
Mounting Set	
Zehnder ComfoWell mounting set, CW-K 520, for Zehnder ComfoAir Q350	990 323 649
Zehnder ComfoWell mounting set, CW-K 520, for Zehnder ComfoAir Q450/600	990 323 646
Filtoro	
Filters Filter for ComfoWell 520, CW-F7 520, ISO ePM1 >80% (F7), 1 Piece	990 323 606

990 323 607

990 323 608

Technical Specification

Filter for ComfoWell 520, CW-F9 520, ISO ePM1 >90% (F9), 1 Piece

Filter for ComfoWell 520, CW-AC 520, active carbon filter, 1 Piece

Housing material	Galvanised Sheet Steel
Operating temperature range	-25 to +60 °C
Inner lining	Closed-cell melamine resin foam
Recommended maximum air volume	111.1l/s (400 m³/h) at normal ventilation level
Air tightness class to EN 1507:2006	С
Air tightness class to EN 12237:2003	С
Fire rating to ISO13501	С

Example Connections

Combination	ComfoAir Q450 right handed with mounting set, 2 x attenuators and 2 x 10 port ø 75mm mounting plates	Stand alone attenuator with 2 x ø 180mm end plates	Stand alone manifold with 1 x ø 180mm end plate and 10 x ø 90mm mounting plate	Stand alone filter housing with 2 x ø 180mm end plate	Stand alone silencer and manifold combined with 1 x ø 180mm end plate and 10 x ø 90mm mounting plate	Stand alone 2 x attenuator with 1 x ø 180mm end plate and 10 x ø 90mm mounting plate
Options Individual Components	Simil modifying piaes		Touring pate		somm mounting plate	Somming pade
Attenuator Article Number: 990 323 502	2 x Zehnder ComfoWell attenuator, CW-S 520	1 x Zehnder ComfoWell attenuator, CW-S 520			1 x Zehnder ComfoWell attenuator, CW-S 520	2 x Zehnder ComfoWell attenuator, CW-S 520
Manifold Box Article Number: 990 323 532			1 x Zehnder ComfoWell manifold box, CW-D 520			
Filter Housing Article Number: 990 323 552				1 x Zehnder ComfoWell filter housing, CW-F 520		
Mounting Plate -ø75 Article Number: 990 323 614	2 x Zehnder ComfoWell mounting plate, CW-M 520, 10 x 75mm connections					_
Mounting Plate -ø90 Article Number: 990 323 615			1 x Zehnder ComfoWell mounting plate, CW-M 520, 10 x 90mm connections		1 x Zehnder ComfoWell mounting plate, CW-M 520, 10 x 90mm connections	1 x Zehnder ComfoWell mounting plate, CW-M 520, 10 x 90mm connections
End Plate - ø 180 Article Number: 990 323 513		2 x Zehnder ComfoWell end plate, CW-P 520, ø 180mm	1 x Zehnder ComfoWell end plate, CW-P 520, ø 180mm	2 x Zehnder ComfoWell end plate, CW-P 520, ø 180mm	1 x Zehnder ComfoWell end plate, CW-P 520, ø 180mm	1 x Zehnder ComfoWell end plate, CW-P 520, ø 180mm
Mounting Set Article Number: 990 323 646	1 x Zehnder ComfoWell mounting set, CW-K 520, for Zehnder ComfoAir Q450/600					
Filter Article Number: 990 323 607				1 x Filter for ComfoWell 520, CW-F9 520, ISO ePM1 >90% (F9), 1 Piece		

Zehnder ComfoWell attenuator, CW-S 520

Article number: 990 323 502



Description


Attenuator:

Zehnder ComfoWell attenuator CW-S 520. Rectangular compact attenuator with highly efficient sound insulation combined with low pressure losses. The attenuator can be used individually or in combination with all ComfoWell components. The airtight connection between components is via a clamping strip.


For cleaning purposes the sound absorbing element can be removed. Mounting on the wall or ceiling is done using the supplied fully adjustable installation mounts.



Side view




Front view



Dimensions

Height	506mm
Width	536mm
Depth	232.5mm
Weight	8.2 kg

Top View



Zehnder ComfoWell manifold box CW-D 520

Article number: 990 323 532

Description

Manifold Box:

Zehnder ComfoWell manifold box CW-D 520. Rectangular compact design with closed pore internal lining. Suitable for use with the mounting plate for ComfoTube 75mm x 10 connections, 90mm x 10 connections or a combination of 90mm x 4 and 75mm x 6 connections. The mounting plate can be mounted on the top or side of the manifold box. The airtight connection between components is via a clamping strip.


For cleaning purposes the manifold box side plate can be removed for easy access. Mounting on the wall or ceiling is done using the supplied fully adjustable installation mounts.



Side view




Front view



Dimensions

Height	233mm
Width	536mm
Depth	259 mm
Weight	5.42 kg

Top View



Zehnder ComfoWell filter housing CW-F 520

Article number: 990 323 552


Description

Filter Housing:


Zehnder ComfoWell filter housing CW-F 520. Rectangular compact design for use with a fine pollen filter graded ISO ePM1 >80% (F7), a fine dust filter graded ISO ePM1 >90% (F9) or an active carbon filter to neutralise odours in the supply air duct run. The filter elements are not included with the filter housing and need to be purchased separately. The filter housing can be used individually or in combination with all ComfoWell components. The airtight connection between components is via a clamping strip.

Mounting on the wall or ceiling is done using the supplied fully adjustable installation mounts.

Side view



Front view



Dimensions

Height	306 mm
Width	536 mm
Depth	242.2 mm
Weight	6.66 kg

Top View



Zehnder ComfoWell mounting plate CW-M 520

Article number: 990 323 614

Description

Mounting Plate:

Zehnder ComfoWell mounting plate CW-M 520-10 x 75. Manifold mounting plate for connection of 10x ComfoTube 75mm semi-rigid ducting.

The mounting plate includes a protective film and the necessary mounting accessories.



Side view




Dimensions

Height	45mm
Width	536mm
Depth	230mm
Weight	<2.42 kg

Front view





Zehnder ComfoWell mounting plate CW-M 520

Article number: 990 323 615

Description

Mounting Plate:

Zehnder ComfoWell mounting plate CW-M 520-10 x 90. Manifold mounting plate for connection of 10 x ComfoTube 90mm semi-rigid ducting.

The mounting plate includes a protective film and the necessary mounting accessories.








Dimensions

Height	45mm
Width	536mm
Depth	230mm
Weight	<2.42 kg



Zehnder ComfoWell mounting plate CW-M 520

Article number: 990 323 617

Description

Mounting Plate:

Zehnder ComfoWell mounting plate CW-M 520 4 x 90 and 6 x 75. Manifold mounting plate for connection of 4 x 90mm and 6 x 75mm semi-rigid ducting.

The mounting plate includes a protective film and the necessary mounting accessories.








Dimensions

Height	45mm
Width	536mm
Depth	230mm
Weight	<2.42 kg





Zehnder ComfoWell end plate CW-P 520 -ø 150

Article number: 990 323 568



Description

End Plate:

Zehnder ComfoWell end plate CW-P 520 - DN150 (with centre connection) for the connection to the ComfoWell attenuator/manifold box or filter housing to the matching ducting size required.

The end plate includes the necessary mounting accessories.

Side view




Front view



Dimensions

Height	42.3mm
Width	536mm
Depth	230mm
Diameter	150mm

Top View



Zehnder ComfoWell end plate CW-P 520 -ø 160mm

Article number: 990 323 564

Description

End Plate:

Zehnder ComfoWell end plate CW-P 520 - DN160 (with centre connection) for the connection to the ComfoWell attenuator/manifold box or filter housing to the matching ducting size required. The end plate includes the necessary mounting accessories.


Side view



Dimensions

Height	42.3mm
Width	536mm
Depth	230mm
Diameter	160mm

Front view



Zehnder ComfoWell end plate CW-P 520 -ø 180mm

Article number: 990 323 513




Description

End Plate:

Zehnder ComfoWell end plate CW-P 520 - DN180 (with centre connection) for the connection to the ComfoWell attenuator/manifold box or filter housing to the matching ducting size required. The end plate includes the necessary mounting accessories.





Front view




Dimensions

Height	42.3mm				
Width	536mm				
Depth	230mm				
Diameter	180mm				

Top View

Ø179.0



Zehnder ComfoWell end plate CW-P 520 -ø 200mm

Article number: 990 323 514

Description

End Plate:

Zehnder ComfoWell end plate CW-P 520 - DN200 (with centre connection) for the connection to the ComfoWell attenuator/manifold box or filter housing to the matching ducting size required. The end plate includes the necessary mounting accessories.

Side view




Front view



Dimensions

Height	42.3mm				
Width	536mm				
Depth	230mm				
Diameter	200mm				

Top View



Zehnder ComfoWell spacer frame, CW-DF 520

Article number: 990 323 539

Description

Zehnder ComfoWell spacer frame CW-DF520. Rectangular frame for use in the event of uneven surfaces when connecting components and mounting plate (concreted in place) are at 90 degrees. The spacer frame includes the necessary mounting accessories.



Front view


Side view



Dimensions

Height	27.8mm
Width	536mm
Depth	230mm
Weight	1.36 ka

Top View



Zehnder ComfoWell mounting set, CW-K 520, for Zehnder ComfoAir Q350

Article number: 990 323 649



Description

Mounting set:

A special mounting set is available for the Zehnder ComfoWell 520 for direct mounting to the ComfoAir Q350 ventilation units. The mounting set includes all the necessary accessories (screws, brackets and mounting brackets).






Dimensions

Height	61.8mm
Width	536mm
Depth	510.5mm
Weight	4.56 kg

Front view



goT	View



Zehnder ComfoWell mounting set, CW-K 520, for Zehnder ComfoAir Q450/600

Article number: 990 323 646



Description

Mounting set:

A special mounting set is available for the Zehnder ComfoWell 520 for direct mounting to the ComfoAir Q450/ComfoAir Q600 ventilation units. The mounting set includes all the necessary accessories (screws, brackets and mounting brackets).

Side view




Front view



Dimensions


Height	61.8mm				
Width	536mm				
Depth	510.5mm				
Weight	5.5 kg				

Top View



Pressure Curve

Comfowell 520



Sound Data

Comfowell 520

Combination	Octave Band (Hz) Insertion Loss, dB							
	63	125	250	500	1000	2000	4000	8000
1 x Attenuator (CW-S 520) with 2 x 180mm end plates (CW-P 520)	2,0	6,3	10,3	16,5	12,0	20,4	15,0	13,5
2 x Attenuator (CW-S 520) stacked with 2 x 180mm end plates (CW-P 520)	6,7	12,3	20,3	22,5	19,2	37,8	27,6	23,9

For use with

Our range of Comfowell units can be used in conjunction with our Zehnder ComfoTube \emptyset 75mm and \emptyset 90mm semi-rigid ductwork.



TO VIEW OUR COMFOTUBE INFORMATION

CLICK HERE

BIM/CAD Components

If you would like to download the BIM / CAD files for this or any other of our products then please visit our BIM library.

TO VISIT OUR BIM/CAD LIBRARY

CLICK HERE

Installation Instructions

If you would like to download the installation files for this or any other of our products then please visit our download page by following the link below.

TO VISIT OUR DOWNLOAD PAGE

CLICK HERE

Consultant specification

Specification

The semi-rigid ductwork manifold shall be constructed of galvanised sheet steel with a closed-cell melamine resin foam inner lining to prevent dust collection and have a fire class C rating according to EN ISO13501.

It shall be of modular construction with options to combine attenuators, manifold box, filter housing with ISO ePM1 >80% (F7), ISO ePM1 >90% (F9) or active carbon filters and end plates ranging from ø 125mm to ø 200mm.

It shall have the option of a mounting set for direct connection to the mechanical ventilation with heat recovery unit. The components shall be tested to BS EN 1507:2006 and BS EN 12237:2003 for airtightness and have removable elements to provide access for cleaning.

